

## CDZ32B Fire Truck



### Technical Specifications

Main technical data in travel configuration				
Category	Item	Unit	Parameter	
Dimension	Overall length	mm	11380	
	Overall	mm	3900	
	Overall	mm	2500	
	Wheel base	Axles 1 and 2	mm	4500
		Axles 2 and 3	mm	1350
	Tread	Front axle	mm	2053
Rear axle		mm	1802	
Weight	Weight with full load	kg	23950	
	Axle load	Front axle	kg	6450
		Dual rear axles	kg	17500
Travel performance	Max. travel speed	km/h	85	
	Min. turning diameter	m	≤24	
	Approach angle	°	16	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

	Departure angle	°	10
	Braking distance(at 30km/h)	m	≤10
	Min. ground clearance	mm	204
	Max. gradeability	%	≥25
Main technical data for operation			
Main performance	Rated working	m	32
	Rated load	kg	400
	Max. working radius (Full extending/semi-extending)	m	19/15
	Outrigger span(longitudinal×lateral)	m	6650×5800
	Elevating range	°	73~80
Working speed	Boom deploying time	S	≤130
	Outrigger extending time	S	≤40
	Slewing speed	r/min	0~1.5
Fire-fighting performance	Water monitor rated flow	L/s	50
	Water monitor rated pressure	MPa	≤1.0
	Water monitor rated reach	m	≥65
	Fire pump rated flow	L/s	50
	Fire pump rated outlet pressure	MPa	1.8

& Due to improvements made to the product, data herein is subject to change without notice.

& Affected by the reproduction conditions, the pictures and data differ somewhat from the actual machine

---

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China  
Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572