

## XCMG GR 260 Motor Grader



<b>GR260</b>	
<b>Basic specification</b>	
Engine model	6CTA8.3—C260
Rated power/speed	194kW/2200rpm
Dimension(LxWxH)	10280×3100×3550mm
Operating weight(Standard)	24000kg
<b>Performance specification</b>	
Travelling speed ,forward	5、 8、 11、 19、 23、 38 km/h
Travelling speed ,reverse	5、 11、 23 km/h
Tractive force(f=0.8)	132KN
Max. gradeability	36%
Tire inflation pressure	350 MPa
Working hydraulic pressure	18 MPa
Transmission pressure	1.3~1.8MPa

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

<b>Operating specification</b>	
Max. steering angle of front wheels	Left / Right 50°
Max. lean angle of front wheels	Left / Right 17°
Max. oscillation angle of front axle	Up / down 15°
Max. oscillation angle of balance box	Before / after 15
Frame articulation angle	Left / Right 27°
Min. turning radius using articulation	8.3m
<b>Blade</b>	
Maximum lift above ground	450mm
Maximum depth of cutting	500mm
Maximum blade position angle	90°
Blade cutting angle	28°—70°
Circle reversing rotation	360°
Moldboard width X height	4572×787mm

Under our policy of continuous product development and improvement ,we reserve the right to change specifications and design without prior notice.

---

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China  
Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572