

XCMG QY130K Truck Crane



Classificatory	Item	Unit	Parameter	
Outline dimension	Overall length	mm	14950	
	Overall width	mm	3000	
	Overall height	mm	3950	
	Axle base	Axle 1, Axle 2	mm	1420
		Axle 2, Axle 3	mm	2420
		Axle 3, Axle 4	mm	1875
		Axle 4, Axle 5	mm	1350
Axle 5, Axle 6		mm	1400	
Wheel base	mm	2610/2307		
Mass	Total mass in travel state	kg	62000	
	Axle load	Axle 1, Axle 2	kg	8800/8800

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

		Axle 3, Axle 4	kg	9200/12700
		Axle 5, Axle 6	kg	12700/9800
Power	Crane superstructure engine	Rated power	kw/(r/min)	162/2100
		Rated torque	N.m/(r/min)	854/1400
		Rated speed	r/min	2100
	Crane carrier engine	Rated power	kw/(r/min)	390/1800
		Rated torque	N.m/(r/min)	2400/1080
		Rated speed	r/min	2000
Travel performance	Travel speed	Max. travel speed	km/h	70
		Min. stable travel speed	km/h	2.1
	Min. turning diameter		m	24
	Min. ground clearance		mm	275
	Approach angle		(°)	23
	Departure angle		(°)	14
	Braking distance (at 30km/h)		m	≤ 10
	Max. grade-ability		%	40
	Fuel consumption for 100km		L	80

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572