

XCMG QY20B.5 Truck Crane



Dimension	Unit	QY20B.5
Overall length	mm	12400
Overall width	mm	2500
Overall height	mm	3300
Weight		
Total weight in travel	kg	26020
Front axle load	kg	6900
Rear axle load	kg	19120
Power		
Engine model		SC8DK260Q3, WD615.327
Engine rated power	kW/(r/min)	192/2200 198/2200
Engine rated torque	N.m/(r/min)	1100/1400 1150/1400
Travel		
Max. travel speed	km/h	75

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Min. turning diameter	m	20
Min. ground clearance	mm	270
Approach angle	°	21
Departure angle	°	11
Max. grade ability	%	35
Fuel consumption for 100km	L	≈35
Main performance		
Max. rated total lifting capacity	t	20
Min. rated working radius	mm	3000
Turning radius at turntable tail	m	3.385
Max. lifting torque	kN.m	860
Base boom	m	10.06
Fully extended boom	m	32.76
Fully extended boom+jib	m	42.12
Longitudinal outrigger span	m	4.97
Lateral outrigger span	m	5.4
Working speed		
Boom luffing time	s	75
Boom full extension time	s	95
Max. swing speed	r/min	3
Max. speed of main winch (single rope)	m/min	100
Max. speed of aux. winch (single rope)	m/min	100

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572