

XCMG QY30K5-1 Truck Crane



Dimension	Unit	QY30K5-1	
Overall length	mm	12570	
Overall width	mm	2500	
Overall height	mm	3390	
Weight			
Total weight in travel	kg	32400	
Front axle load	kg	7000	
Rear axle load	kg	25400	
Power			
Engine model		SC8DK280Q3	WD615.329
Engine rated power	kW/(r/min)	206/2200	213/2200
Engine rated torque	N.m/(r/min)	1112/1400	1160/1400

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Travel		
Max. travel speed	km/h	80
Min. turning diameter	m	22
Min. ground clearance	mm	291
Approach angle	°	19
Departure angle	°	13
Max. grade ability	%	40
Fuel consumption for 100km	L	40
Main performance		
Max. rated total lifting capacity	t	30
Min. rated working radius	mm	3000
Turning radius at turntable tail	m	3.065
Max. lifting torque	kN.m	1025
Base boom	m	10.6
Fully extended boom	m	40.4
Fully extended boom+ jib	m	48.7
Longitudinal outrigger span	m	5.85
Lateral outrigger span	m	6
Working speed		
Boom luffing time	s	68
Boom full extension time	s	150
Max. swing speed	r/min	2.5
Max. speed of main winch (single rope) (no load)	m/min	120
Max. speed of aux. winch (single rope) (no load)	m/min	120

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572