

XCMG QY40K Truck Crane



Dimension	Unit	QY40K
Overall length	mm	13050
Overall width	mm	≤2800
Overall height	mm	3430
Weight		
Total weight in travel	kg	40400
Front axle load	kg	14500
Rear axle load	kg	25900
Power		
Engine model		WD615.334
Engine rated power	kW/(r/min)	247 / 2200
Engine rated torque	N.m/(r/min)	1350 / 1400

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Travel		
Max. travel speed	km/h	75
Min. turning diameter	m	≤24
Min. ground clearance	mm	285
Approach angle	°	16
Departure angle	°	11
Max. grade ability	%	46
Fuel consumption for 100km	L	46
Main performance		
Max. rated total lifting capacity	t	40
Min. rated working radius	mm	3000
Turning radius at turntable tail	m	3.482
Max. lifting torque	kN.m	1400
Base boom	m	10.7
Fully extended boom	m	40.1
Fully extended boom+ jib	m	55.1
Longitudinal outrigger span	m	5.65
Lateral outrigger span	m	6.6
Working speed		
Boom luffing time	s	≤88
Boom full extension time	s	≤180
Max. swing speed	r/min	≥2.0
Max. speed of main winch (single rope)	m/min	≥110
Max. speed of aux. winch (single rope)	m/min	≥110

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572