

XCMG QY70K-I hydraulic control Truck Crane



Dimensions	Unit	
Overall length	Mm	14155
Overall width	Mm	2800
Overall height	Mm	3675
Weight		
Dead weight in travel state	Kg	44490
1st.2nd axle load	Kg	9245
3rd.4th axle load	Kg	26000
Power		
Carrier engine		WD615.338
Engine rated output	Kw(r/min)	276/2200

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Travel		
Max.travel speed	Km/h	80
Min. turning diameter	M	24
Min. ground clearance	Mm	324
Approach angle	°	21
Departure angle	°	14
Max. gradeability	%	40
Fuel consumption of per 100km	L	45
Lifting performance		
Max. total rated lifting capacity	T	70
Min. rated working radius	M	3
Turning radius at swing table tail	Mm	3857
Base boom max. load moment	Kn.m	2676
Base boom	M	11.8
Full-extend boom	M	45
Full-extend boom+Jib	m	61
Outrigger longitudinal distance span	M	6.1
Outrigger lateral distance span	M	7.3
Working speed		
Boom elevating time	S	60
Boom telescoping time	S	150
Max. slewing speed	r/min	2
Main winch max. speed(single line)	m/min	130
Auxiliary winch max.speed(single line)	m/min	108

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572