

XCMG RP601 Road Paver



Items	Unit	Parameters
Basic paving width	m	2.5
Max. paving width	m	6
Max. paving thickness	mm	150
Paving speed	m/min	0~3.6
Travel speed	km/h	0~11
Theoretical Productivity	t/h	300
Hopper Capacity	t	13
Gradeability	%	20
Pavement evenness	mm/3m	3
Transverse levelling accuracy	%	±0.03
Centre crown ratio	%	0~+3

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Engine model		D4114ZG2B
Engine power	kW	100
Engine speed	r/min	2400
Machine weight	t	17.4
Dimension	mm	6400X2580X3830
Vibrator speed	r/min	0~1470
Screed heating		Gas heating
Auger and conveyor control		Automatic Control by Ultrasonic Sensors
Automatic levelling control		Simulation control of electronic automatic leveler

Items	Unit	Parameters
Screed model	/	475Q
Type	/	Single vibrator+Gas heating
Extension	/	Hydraulic+Mechanical assembly
Width	m	2.5~6.0
Vibrator speed	r/min	0~1470
Vibrator amplitude	mm	4

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572