

## XCMG RP602 Road Paver



Item	Unit	RP602
Basic paving width	m	2.5
Max. paving width	m	6
Max. paving thickness	mm	380
Paving speed	m/min	0~14
Travel speed	km/h	0~3.0
Theoretical productivity	t/h	400
Hopper capacity	t	13
Gradeability	%	20
Pavement evenness	mm/3m	3
Cross slope error	%	±0.03
Crown adjustment range	%	0~3
Diesel engine model		BF4M1013C

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China  
Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Diesel engine power	kw	118
Diesel engine speed	r/min	2300
Diesel oil tank capacity	L	230
Overall weight	t	15.8~21.5
Dimension	mm	6230×2500×3855
Vibration frequency	Hz	/
Screed heating mode		Electrical heating
Material level control mode		Automatic Control by Ultrasonic Sensor
Automatic Leveling Control		Simulation control

Item	Unit
Screed model	475(RP602)
Type	Vibration, electrical heating
Stretch mode	Hydraulic stretch
Width range	2.5-6.0m
Vibrating tamper rotate speed	0-1500r/min
Vibration frequency	4mm

---

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China  
Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572