

## XCMG RP701J Road Paver



### Technical Specifications

Items	Unit	Parameters
Model		R701J
Basic paving	m	2.5
Max. paving	m	6/7
Max. paving thickness	mm	300
Paving speed	m/min	2.0~5.98
Travel speed	km/h	1.52~4.55
Theoretical Productivity	t/h	400
Hopper Capacity	t	13
Gradeability	%	20
Pavement evenness	mm/3m	3(Asphalt)/5(Stabilized soil)
Transverse levelling accuracy	%	0.02
Engine model	/	YC6108G
Engine Parameters	kW/rpm	92/2300
Fuel tank capacity	L	160
Machine weight	t	19.3

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Dimension	mm	6636 × 2580 (3000) × 3680
-----------	----	---------------------------

& Due to improvements made to the product, data herein is subject to change without notice.

& Affected by the reproduction conditions, the pictures and data differ somewhat from the actual machine

---

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572