

XCMG RP952 Road Paver



Item	Unit	RP952
Basic Paving Width	m	3
Max Paving Width	m	9.5
Max Paving Thickness	mm	350
Paving Speed	m/min	0~16.5
Travel Speed	km/h	0~2
Theoretical Productivity	t/h	700
Capacity	t	14
Hopper Capacity	%	20
Gradeability	mm ³ m	≤3
Pavement Evenness	%	±0.03
Transverse Leveling Accuracy	%	-1~3
Centre Crown Ratio		

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Engine Model		D6114ZG1B
Engine Power	kw	140
Engine Speed	r/min	2300
Diesel Tank Capacity	L	270
Machine Weight	t	21.3~28.8
Tamper Vibration Frequency	Hz	0~50
Screed Heating		Gas Heating
Auger and Conveyor Control		Automatic Control by Ultrasonic Sensors
Automatic Leveling Control		Simulation

Screed model	Type	Stretching method	Width range	Vibrating speed	Main amplitude	Auxiliary amplitude
DTV-I(RP951A)	Dual-vibrating, eccentric vibrating, electric heating	Mechanical assembly	3.0-9.5m	0-1470r/min	3,5,7,9mm	0,3,6,9,12mm
DTQ-I(RP952)	Dual-vibrating, gas heating	Mechanical assembly	3.0-9.5m	0-1470r/min	3,5,7,9mm	0,3,6,9,12mm
EDV60D (RP902)	Dual-vibrating, eccentric vibrating, electric heating	Hydraulic variomatic	3.0-9.5m	0-1470r/min	5mm	0,5,10mm

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572