

## XCMG XD 111E Tandem Vibratory Roller



Type	Unit	XD111E
Operating weight (including cab)	kg	11300
load on front drum	kg	5650
Load on rear wheels	kg	5650
Static linear load	N/cm	298/298
Speed	km/h	0—10
Gradeability in theory	%	30
Minimum turning radius	mm	4050/5950
Crab-walking distance	mm	160
Minimum ground clearance	mm	340
Wheel base	mm	3700
Steering angle	± °	35

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China  
Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Swing angle	±°	8
Vibration frequency	Hz	45—48
Nominal amplitude	mm	0.41/0.8
Centrifugal force	kN	80/133
Model and manufacturer		DEUTZ BF4M2012C
Rated rotating speed	r/min	2300
Rated power	kW	98
Rated oil wear	g.kw/h	205
Water tank capacity	L	2×450
Fuel tank capacity	L	210

---

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China  
Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572