

## XCMG XE135B Excavator



Model		Unit	XE135B
Operating weight		kg	13800
Standard bucket capacity		m <sup>3</sup>	0.4-0.52
Engine	Engine Model	/	ISUZU BB-4BG1TRP
	Direct injection	/	√
	Four strokes	/	√
	Water cooling	/	√
	Turbo charged	/	√
	Air to air intercooler	/	×
	No. of cylinders	/	4
	Rated power/speed	kw/rpm	69.6/2200
	Max. torque/speed	N.m	337.6
	Displacement	L	4.329

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China  
Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

The main performance	Travel speed	km/h	5.16/3.03
	Swing speed	r/min	12.3
	Max. gradeability	/	≥35
	Ground pressure	kPa	42
	Max.Bucket digging force	kN	85
	Max.arm crowd force	kN	65
	Max.traction force	kN	134
Hydraulic system	Main pump	/	2 个柱塞泵
	Rate flow of main pump	L/min	2×123
	Max pressure of prime relief valve	MPa	31.4/34.3
	Max pressure of travel system	MPa	34.3
	Max pressure of swing system	MPa	25
	Max pressure of pilot system	MPa	3.9
Oil capacity	Fuel tank capacity	L	250
	Hydraulic tank capacity	L	130
	Engine lubrication	L	14
Overall dimensions	A Overall length	mm	7770
	B Overall width	mm	2512
	C Overall height	mm	2880
	D Overall width of upperstructure	mm	2512
	E Track length	mm	3660
	F Overall width of undercarriage	mm	2490
	G Crawler width	mm	500
	H Track length on ground	mm	2910
	I Crawler gauge	mm	1990
	J Clearance under counter weight	mm	964
	K Ground clearance	mm	478

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China  
Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

	L Min.tail swing radius	mm	2294
Working range	A Max. digging height	mm	8641
	B Max. dumping height	mm	6181
	C Max. digging depth	mm	5538
	D 8inch horizontal digging depth	mm	5287
	E Max. vertical wall digging depth	mm	4727
	F Max. digging reach	mm	8296
	G Min. swing radius	mm	2335
	Angle of arm deflection	Degree	—

---

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China  
Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572