

XCMG XE265C Excavator



Model	Unit	XE265C	
Operating weight	kg	25500	
Standard bucket capacity	m ³	1.05~1.25	
Engine	Engine Model	/	ISUZU CC-6BG1TRP
	Direct injection	/	√
	Four strokes	/	√
	Water cooling	/	√
	Turbo charged	/	√
	Air to air intercooler	/	√
	No. of cylinders	/	6
	Rated power/speed	kw/rpm	128.5/2100
	Max. torque/speed	N.m	637/1800

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

	Displacement	L	6.494
The main performance	Travel speed	km/h	5.9/4.0
	Swing speed	r/min	11.3
	Max. gradeability	/	≤35
	Ground pressure	kPa	50.1
	Max.Bucket digging force	kN	161
	Max.arm crowd force	kN	125
	Max.traction force	kN	194
Hydraulic system	Main pump	/	2 Plunger pump
	Rate flow of main pump	L/min	2×256
	Max pressure of prime relief valve	MPa	34.3/37
	Max pressure of travel system	MPa	34.3
	Max pressure of swing system	MPa	28
	Max pressure of pilot system	MPa	3.9
Oil capacity	Fuel tank capacity	L	400
	Hydraulic tank capacity	L	240
	Engine lubrication	L	25
Overall dimensions	A Overall length	mm	10160
	B Overall width	mm	3190
	C Overall height	mm	3100
	D Overall width of upperstructure	mm	2830
	E Track length	mm	4640
	F Overall width of undercarriage	mm	3190
	G Crawler width	mm	600
	H Track length on ground	mm	3842
	I Crawler gauge	mm	2590
	J Clearance under counter weight	mm	1100

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

	K Ground clearance	mm	485
	L Min.tail swing radius	mm	2985
Working range	A Max. digging height	mm	9662
	B Max. dumping height	mm	6810
	C Max. digging depth	mm	6895
	D 8inch horizontal digging depth	mm	6750
	E Max. vertical wall digging depth	mm	5480
	F Max. digging reach	mm	10240
	G Min. swing radius	mm	3850
	Angle of arm deflection	Degree	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572