

XCMG XE335C Excavator



Model		Unit	XE335C
Operating weight		kg	33800
Standard bucket capacity		m ³	1.4~1.6
Engine	Engine Model	/	ISUZU AA-6HK1XQP
	Direct injection	/	√
	Four strokes	/	√
	Water cooling	/	√
	Turbo charged	/	√
	Air to air intercooler	/	√
	No. of cylinders	/	6
	Rated power/speed	kw/rpm	184/2000
	Max. torque/speed	N.m	872.8/2000

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

	Displacement	L	7.79
The main performance	Travel speed	km/h	5.5/3.3
	Swing speed	r/min	9.7
	Max. gradeability	/	≥35
	Ground pressure	kPa	66
	Max. Bucket digging force	kN	225
	Max. arm crowd force	kN	183
	Max. traction force	kN	261
Hydraulic system	Main pump	/	2个柱塞泵
	Rate flow of main pump	L/min	2×280
	Max pressure of prime relief valve	MPa	31.5/34.3
	Max pressure of travel system	MPa	34.3
	Max pressure of swing system	MPa	27.5
	Max pressure of pilot system	MPa	3.9
Oil capacity	Fuel tank capacity	L	630
	Hydraulic tank capacity	L	320
	Engine lubrication	L	28
Overall dimensions	A Overall length	mm	11246
	B Overall width	mm	3190
	C Overall height	mm	3330
	D Overall width of upperstructure	mm	2960
	E Track length	mm	4725
	F Overall width of undercarriage	mm	3190
	G Crawler width	mm	600
	H Track length on ground	mm	3183
	I Crawler gauge	mm	2590
	J Clearance under counter weight	mm	1170

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

	K Ground clearance	mm	495
	L Min.tail swing radius	mm	3450
Working range	A Max. digging height	mm	10404
	B Max. dumping height	mm	7256
	C Max. digging depth	mm	7158
	D 8inch horizontal digging depth	mm	6935
	E Max. vertical wall digging depth	mm	6526
	F Max. digging reach	mm	10887
	G Min. swing radius	mm	4424
	Angle of arm deflection	Degree	2.9m bucket rod

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572