



Main technical specifications	unit	XMR155
Operating weight	kg	1600
Distributed weight in vibration drum(front/rear)	kg	800/800
Static linear load(front/rear)	N/cm	88/88
Speed	km/h	0-9
Gradeability	%	30
min turning radius (out)	mm	2700
min ground clearance	mm	250
wheel base	mm	1350
steering angle		34°
swing angle		7°
vibration frequency	Hz	70
nominal amplitude	mm	0.4
centrifugal force	KN	17

Shanghai Longji Construction Machinery Co., Ltd.

**Add:** Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

**Post Code:** 201100

**E-mail:** [info@shlongji.com](mailto:info@shlongji.com)

**Tel:** +86-21-541-71571

**Fax:** +86-21-541-71572

**Website:** [www.shlongji.com](http://www.shlongji.com) Wheel Loader,Road Roller,Dump Truck

drum diameter	mm	582
compacting width	mm	893
Engine model		perkins 403D-11
Rated speed	r/min	2600
Rated power	kw	17.3
Overall dimensions	mm	2118*977*2279
Rated oil wear	g/kw.h	235
Fuel tank capacity	L	15
Hydraulic tank capacity	L	24
Sprinkler capacity	L	110

Shanghai Longji Construction Machinery Co., Ltd.

**Add:** Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

**Post Code:** 201100

**E-mail:** [info@shlongji.com](mailto:info@shlongji.com)

**Tel:** +86-21-541-71571

**Fax:** +86-21-541-71572

**Website:** [www.shlongji.com](http://www.shlongji.com) Wheel Loader,Road Roller,Dump Truck