

XCMG XS162J Single Drum Vibratory Roller



Model	Unit	XS162J
Operating weight	kg	16000
Weight on front drum	kg	7700
Static linear pressure	N/cm	362
Speed range	km/h	
Speed I		2.54
Speed II		4.97
Speed III		10.51
Theoretical gradeability	%	30
Min. external turning radius	mm	6500
Steering angle	°	±33
Oscillating angle	°	±11
Vibration frequency	Hz	28

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Nominal amplitude (high/low)	mm	1.9/0.95
Excitation force (high/low amplitude)	kN	290/145
Engine model		SC8D156.2G2B1
Type	Water cooled, pressurized	Water cooled, pressurized
Max. power	kW	115@1800r/min
Engine oil consumption	g/kW.h	223
Hydraulic oil tank capacity	L	170
Fuel tank capacity	L	240

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572