

XCMG XS 222 Single Drum Vibratory Roller



Type	Unit	XS222
Operating weight	kg	22000
Load on front drum	kg	15000
Load on rear wheels	kg	7000
Drum width	mm	2130
Static linear load	N/cm	704
Vibration frequency(Low/High)	Hz	28/33
Nominal amplitude(High/Low)	mm	1.86/0.93
Excitation force(High/Low)	KN	390/270
Travel speed	km/h	0~10
Steering angle	°	±33
Swing angle	°	±10
Theoretical gradeability	%	50

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Min. external turning radius	mm	6500
Engine model		Cummins B5.9
Engine power	kw	132
Rated engine speed	r/min	2200
Engine oil consumption	g/kW.h	232
Hydraulic oil tank capacity	L	240
Fuel tank capacity	L	240

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572