

XCMG XS 262J Single Drum Vibratory Roller



Technical Specifications

Item	Unit	XS262J
Operating weight	kg	26000
Weight on front drum	kg	13000
Static linear load	N/cm	582
Speed range	km/h	
Speed I		2.52
Speed II		4.95
Speed III		8.1
Theoretical gradeability	%	35
Min. external turning radius	mm	6800
Steering angle	°	±33
Oscillating angle	°	±10
Vibration frequency (high/low)	Hz	32/27
Nominal amplitude (high/low)	mm	1.9/0.95
Excitation force (high/low amplitude)	kN	405/290
Drum diameter	mm	1600
Drum	mm	2170
Engine model		Shanghai Diesel Engine SC8D190.2G2
Rated power @2000 r/min	kW	140
Engine oil consumption	g/kW.h	223
Hydraulic oil tank capacity	L	170

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Fuel tank capacity	L	320
--------------------	---	-----

& Due to improvements made to the product, data herein is subject to change without notice.

& Affected by the reproduction conditions, the pictures and data differ somewhat from the actual machine

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572